

PACi Low Static Ducted

Product Code: S-140PN1E5A

14.0kW - PACi Low Static Ducted Indoor Unit - Split - R410A

Notes

- » Compact indoor units without losing static pressure (Only 250mm high)
- » 50 Pa static pressure
- » Easy maintenance and service via external electrical box
- » 3 speed centrifugal fan through wired or wireless remote control
- » DC FAN for better efficiency and control
- » Easy connection and control of external fan or ERV using the connector PAW-FDC on the indoor unit PCB. The external device can be control by the remote



MODEL NUMBER		S-140PN1E5A
GRILLE		NA
Nominal cooling	kW	14
Nominal heating	kW	14
Height	mm	250
Width	mm	1200
Depth	mm	650
Weight	kg	41
Knock out for fresh air intake		NA
Knock out for branch duct		NA
Indoor unit airflow rate (l-h)	l/s	500 - 617 - 667 (L - M - H)
Moisture Removal Volume	l/h	9
Static pressure	pa	50 (10 - 80)
Spigot Kit		AMP-PN4DUCT
Discharge spigot		4 x 200mm
Sound pressure level (l-m-h)	dB(A)	39 - 44 - 46
Pipe connection size - gas	in	5/8"
Pipe connection size - liquid	in	3/8"
Refrigerant		R410A
Drain connection	mm	TBC
Lift pump?		No
Power supply	V-Ph-Hz	230-1-50
Interconnecting cables		2 core
Suggested fuse size		5
Controller included?		No
* exact cooling and heating capacities will depending on connected outdoor unit and system configuration		

